

## Product Information Declaration

# Tarkett Acczent Excellence Range

### Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as Tarkett Acczent Excellence

### Identifiers

See individual sku codes under [identifiers](#)

### Scope and Limitations of Intended Use

✓ Residential	✓ Commercial	✓ Interior	✗ Exterior
✓ High Traffic	✗ Low-Traffic	✓ Exposed Sunlight	✗ Wet Areas
✗ Antistatic Environment	✗ Food-Prep Areas	✗ Clean-Room	✓ With Wheels
✗ Ramp/Entry	✓ Under Floor Heating	✗ Over Existing Floor	

## B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	10 years
Residential	-
Commercial	34 (ISO 18074)
Industrial	43 (ISO 18074)

## C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CRF 8.12 kW/m2 (ISO 9239-1)

## D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	Refer to Slip Test Summary Sheet
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

## E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

## F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	Less than 10-µg/m3 (ISO 16000-9)
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

## G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	delta Lw 3 dB (EN ISO 717-2)

## H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	0.02m2 K/W (EN ISO 10456)

## X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

## Supporting Documents

All supporting documents can be found on the Jacobsen website, [jacobsen.co.nz](http://jacobsen.co.nz) or by this QR code



# Product Information Declaration

## Tarkett Acczent Excellence Range

---

### **B2.3.1**

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)  
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
  2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

### **C3.4**

Surface Linings

#### **(b)**

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### **D1.3.3**

Access routes shall:

#### **(d)**

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### **E3.3.3**

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### **E3.3.5**

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### **E3.3.6**

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

### **F2.3.1**

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

### **G3.3.2**

Spaces for food preparation and utensil washing shall have:

#### **(b)**

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### **G6.3.1**

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### **G6.3.2**

The Impact Insulation Class of floors shall be no less than 55.

### **H1**

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

---

## Note

It is expected that Tarkett Acczent Excellence is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

# Product Information Declaration

## Tarkett Acczent Excellence Range

### Identifiers

This JPID covers all colours from Tarkett Acczent Excellence including:

Triangle Wood Chalk E25128136	Concrete Steel Blue E25128507
Soft Water E25128134	Concrete Warm Grey E25128504
Warm Grey E25131925	Concrete Grey Beige E25128503
Dark Beige E25131918	Serene Oak Medium Grey 0508 E25204508
Medium Grey 24481	Intense Jean 23267
Brushed Grey E25130100	Intense Terracotta 22944
Allover Wood White E25129714	Bright Extreme Blue E25131941
Allover Wood Black E25129713	White 24483
Carpet Intense Olive E25128106	Black 23913
Terrazzo Blue E25128105	White E25127817
Terrazzo Terracotta 0104 E25128104	Beech Longstripe Light 21993
Tissage Soft Orange E25128132	Brushed Oak Light E25127027
Tissage Soft Light Green E25128131	Brushed Oak Medium E25127026
Tissage Soft Light Blue E25128130	Oak Longstripe Natural 7002 19088
Tissage Soft Beige E25128129	Oak Longstripe Light 7001 21484
Tissage Soft Grege E25128128	Matrix Phospho 0101 E25032101
Tissage Soft Grey E25128127	Facet Black & White E25128118
Tapped Metal Grey 0126 E25128126	Facet Mid Grey E25128116
Dark Grey 24477	Facet Water E25128115
Matrix Bright Orange 0188 E25131188	Fusion Lines Intense Olive E25130175
Matrix Bright Anis 0186 E25131186	Fusion Lines Intense Petrole E25130174
Matrix Bright Turquoise 0185 E25131185	Fusion Lines Beige E25130173
Matrix Dark Grey 1019 E25131019	Fusion Lines Dark Grey E25130172
Matrix Graphite E25131000	Fusion Lines Phospho E25130171
Digital Wave Grey Anis E25130184	Concrete Chalk E25128502
Allover Wood Grege 12212	Concrete Dark Grey 12207
Scandinavian Medium Beige 0403 E25129403	Concrete Grey Beige 19007
Scandinavian Light Beige 0402 E25129402	Fiber Wood Natural E25128303
Scandinavian Medium Grey 0401 E25129401	Fiber Wood Grege E25128302
Scandinavian Oak Dark Grey 0400 E25129400	Encryption Black & White E25128189
Oak Tree Grey 0202 E25129202	Flocons 2 Rainbow E25128170
Oak Tree Beige 12211	Intense Olive E25131938
Serene Oak Dark Brown 0512 22224	Intense Water E25131936
Serene Oak Warm Brown 0511 E25204511	Intense Petrole E25131935
Serene Oak Red Brown 0510 E25204510	Intense Kaki 24480
Serene Oak Brown Grey 0509 E25204509	Bright Dark Turquoise E25131933
Terrazzo Green 0103 E25128103	Bright Ice Blue E25131932
Esquisse Light Chocolate E25128017	Modern Oak Natural Brown E25029009
Esquisse Dark Grey E25128015	Granito Cool Grey 23011
Esquisse Medium Grey E25128014	Granito Warm Grey 21451
Esquisse Light Grey E25128013	Granito Light Beige E25128109
Esquisse Grey Beige E25128012	Carpet White Grey E25128108
Natural E25127818	Carpet Intense Jean 12204
Diamond Blue E25128123	Cubic Intense Petrole E25130166
Facet Prune E25128121	Cubic Bright Anis E25130164
Facet Blue 12205	Bubbles Cold Mix E25130143
Digital Wave Grey E25130183	Modern Maple Maple 0141 22191
Digital Wave Grey Ice Blue E25130182	Indigo E25128140
Modern Oak Natural 19011	Turquoise E25128139
Modern Oak Grege 12209	Dark Grey 21450
Modern Oak White E25129005	Triangle Wood Natural E25128137
	Bright Anis E25131931
	Bright Yellow 24034
	Bright Orange E25131929
	Bright Red 24474
	Bright Pink E25131927
	Bright Turquoise E25131926

### Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Point
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		8.78 kgCO <sub>2</sub> e / m <sup>2</sup> (Cradle to Gate)

### Environmental Credentials



