Product Information Declaration

Tarkett Traffic 250 Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the vinyl range sold by Jacobsen as **Tarkett Traffic 250**

Identifiers

See individual sku codes under identifiers

Scope and Limitations of Intended Use

<u> </u>	Residential	
<u> </u>	High Traffic	

______<u>`</u>

X Antistatic Environment
X Remp/Entry

/ Commercial

✓ Food Prep Areas

Under Floor Heating

Interior

✓ Exposed Sunlight

X Clean Room

X Over Existing Floor

Exterior

✓ Wet Areas

✓ With Wheels

R

Stability

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	10 years Commercial / 15 years Residential	
Residential	Extra Heavy Duty	
Commercial	34 Heavy Duty	
Industrial	43 Heavy	

Protection from Fire

Relevant NZBC Clause	Product Performance	
C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	7.5 kW/m2 (ISO 9239.1:2010)	

Access

Relevant NZBC Clause	Product Performance	
D1.3.3		
Level Surface (Wet)	SRV 33 (AS/NZS 4586:2013)	
Level Surface (Dry)	Acceptable Solution	
Suitable for food prep	_	

E

Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F

Safety of Users

Relevant NZBC Clause	Product Performance	
F2.3.1	Gold,≤ 100μg/m3 (EN 16516)	
	Does not encourage bacterial growth	
	Phthalate-free	
Indoor Air Quality	Optimal	

G

Services and Facilities

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	14 dB (ISO 717/2)	

H

Energy Efficiency

Relevant NZBC Clause	Product Performance	
Thermal Rating	0,020 m ² •K/W (ISO 10456)	

X

Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Page 1 of 3 V:140524

Product Information Declaration Tarkett Traffic 250 Range

B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

(c)

5 years if:

- 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
- 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Tarkett Traffic 250** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Page 2 of 3 V:140524

Product Information Declaration Tarkett Traffic 250 Range

Identifiers

This JPID covers all colours from Tarkett Traffic 250 including:

Swan Gold 25300 Swan Walnut 25302 Swan Russet 25163 Swan Driftwood 25162 Kiruma Cinders 25161 Antik Oak Kaolin 25160 Antia Light Grege 25296 Terrazzo Matera Clay 25238 Terrazzo Matera Graphite 25166 Swan Blonde 25165 Swan Hazel 25164 Concrete - Charcoal 19168 Winter Pine - Smoke 17113
Kiruma - Pearl Grey 17111
Kiruma - Black Grey 17110
Warm Oak - Soft Brown 17108
Winter Pine - Soft Beige 17107
Winter Pine - Soft Natural 17106
Winter Pine - Soft Grey 17105
Arcadia - Brown Natural 17102
Soft Elm - Natural 17101
Antik Oak - Light Natural 17100
Soft Elm - Dark Grey 17099
Antik Oak - Light Brown 17097

Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	-
As Built NZ (V1)	Credit 20	-
	Credit 21	Sustainability Factor (SF) = 1
Green Star	Credit 13	-
Interiors NZ (V1)	Credit 20	-
	Credit 21	Sustainability Factor (SF) = 1
Green Star Performance NZ (V1)	Credit 21	1 Point
Homestar V5	HC 7	1 Point
	EN 3	1.5 Points
Homestar V4	Mat-1	2 Points
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		6.83 kgCO2e / m2 (Cradle to Gate)

Environmental Credentials





























Jacobsen®

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN:

9429040403328

OTarkett

Product Manufacturer: Tarkett Country of Origin: Luxembourg

Page 3 of 3 V:140524