# Jacobsen®

## **Product Information Declaration**

## TimberTop Range

#### **Range Description**

This Jacobsen Product Information Declaration (PID) applies to the wood range sold by Jacobsen as TimberTop

#### Scope and Limitations of Intended Use

~	Residential	
~	High Traffic	
×	Antistatic Environment	

X Ramp/Entry

X Low Traffic X Food Prep Areas

**Under Floor Heating** 

1

Commercial

Interior
Exposed Sunlight
Clean Room

**Identifiers** 

See individual sku codes under identifiers

X Over Existing Floor

- X Exterior
- X Wet Areas
- With Wheels

## B

#### Stability

Relevant NZBC Clause	Product Performance	
B2.3.1(c)	25 years Residential, 5 years Commercial	
Residential	-	
Commercial	-	
Industrial	-	

#### **C** Protection from Fire

Relevant NZBC Clause	Product Performance	
C4.3		
C4.3 (a) Wall	-	
C4.3 (b) Floor	4.3kW/m2 (ISO 9239.1:2010)	

### D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

### Ε

#### Moisture

Relevant NZBC Clause	Product Performance	
E3.3.3	Impervious and easily cleaned	
E3.3.5	Impervious and easily cleaned	
E3.3.6	Water resistant	
NZBC/AS1	-	

## F

#### **Safety of Users**

Relevant NZBC Clause	Product Performance	
F2.3.1	≤ 0.5 mg/m3	
	-	
	Phthalate-free	
Indoor Air Quality	Optimal	

## G

#### **Services and Facilities**

Relevant NZBC Clause	Product Performance	
G3.3.2 (b)	Water resistant	
G6.3.2	-	

### H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

### **X** Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

#### **Supporting Documents**

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



## **Product Information Declaration TimberTop Range**

#### B2 3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

#### (c)

5 years if: 1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and

2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

#### C3.4

Surface Linings

#### (b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

#### D1.3.3

Access routes shall:

#### (d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

#### E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

#### E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

#### E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

## Note

It is expected that **TimberTop** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

#### F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

#### G3.3.2

Spaces for food preparation and utensil washing shall have:

#### (b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

#### G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

#### G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

#### H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

### **Product Information Declaration TimberTop Range**

#### **Identifiers**

This JPID covers all colours from TimberTop including:

Tenerife XL Rustic 2450mm x 240mm 26816 Absolute XL Rustic 2450mm x 240mm 22936 Banff Rustic 2130mm x 190mm 21391 Coronet Peak Rustic 2130mm x 190mm 21390 Mykonos Lifestyle 2130mm x 190mm 21389 Aspen Lifestyle 2130mm x 190mm 21387 Bahamas Lifestyle 2130mm x 190mm 21386 Mauritius Lifestyle 2130mm x 190mm	Absolute Rustic 2130mm x 240mm 21384 Tenerife Rustic 2130mm x 240mm (currently ltd stock avail in this size) 21383 Smoked Neutrino Rustic 2130mm x 240mm 21382 Puerto Rico Lifestyle 2130mm x 240mm 21380 Bequia Lifestyle 2130mm x 240mm 21339 Cayman Lifestyle 2130mm x 240mm 21338 Montserrat Lifestyle 2130mm x 240mm 21337 Brackenridge 1820mm x 145mm 22650
21386 Mauritius Lifestyle 2130mm x 190mm 21385	21337 Breckenridge 1820mm x 145mm 22650

#### Sustainability

Rating System	Rating	Product Performance
Green Star Design &	Credit 12	1 Point
As Built NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star	Credit 13	1 Point
Interiors NZ (V1)	Credit 20	1 Point
	Credit 21	Sustainability Factor (SF) = 0.75
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		Yes
Embodied Carbon Emission Data		-2.20kg Co2/m2 Cradle to Gate

#### **Environmental Credentials**



## **Jacobsen**<sup>®</sup>

Jacobsen 41D Morrin Road, St Johns, 1072 0800 800 460 jacobsen.co.nz sales@jacoben.co.nz

NZBN: 9429040403328 Product Manufacturer: Forestry Timber Country of Origin: Malaysia