

SHAW 8300 SEAM SEALER

MOISTURE IMPERVIOUS CARPET SEAM SEALER

Any variance from these procedures will become the responsibility of the installer and manufacturer. For specific questions regarding Shaw 8300 not covered within this document please contact Technical Support at . Shaw requires the use of seam sealer on all carpet products with the exception of carpet tile. Shaw 8300 is a polymer-fortified, nonflammable seam sealer recommended for sealing cut edges of broadloom to prevent raveling, and provides a moisture impervious seam when applied properly.

FEATURES AND BENEFITS

- Applies easily with applicator tip
- CRI Green Label Plus certified and SCAQMD compliant (solvent free)
- Moisture impervious passing the British Spill Test (when applied properly)

Weight	Pallet Qty.	Pallet Weight
(12) 8 oz. / 8.5 lbs.	100 cases	900 lbs.

Laboratory Tests	Results
Polymer type	Latex polymer
Percent solids	50-52%
VOCs Rule #1168 of California's SCAQMD	6 g/L
Roll-ability	Easy
Density	8-9 lbs.
Consistency	Paste
Colour	White, dries clear
Tracer	UV fluorescent
Shelf life	Mild
Storage conditions	1 year when stored in original packaging at 73°F (23°C)
Flash point (ASTM D56)	65°F to 95°F (18°C to 35°C)
Protect from traffic	30 minutes

Although the adhesive is freeze/thaw stable, protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

ENVIRONMENTAL

- Meets the requirements of California South Coast Air Quality Management District Rule 1168
- Meets the requirements of California Department of Public Health Section 01350
- CRI Green Label Plus Certified #59126

LEED IEQ Credit Information (2009 and V4)

Credit Requirement	Status	Comment
Meet General Emissions Evaluation Criteria	Complies	CRI Green Label Plus (GLP) # 59126
VOC's (Rule #1168 of California SCAQMD amended October 6, 2017)	Complies	VOC Content < 50g/L

1-YEAR WARRANTY

This product is covered by a 1-year limited warranty. For information on this limited warranty, please ask your authorised Shaw retailer or contact .

APPROXIMATE PRODUCT COVERAGES

Coverages shown are for estimating purposes only. Actual jobsite coverages may vary according to applicator tip size and application.

Application	Coverage
1/8" bead	138-150 lf

APPLICATION

- Prepare carpet according to Shaw Industries Installation Guidelines.
- Apply a bead of seam sealer along the carpet primary backing on one side of the carpet applicator tip provided with the bottle.
- Complete the seam by butting both sections of the carpet together while the seam sealer is still wet (within 5 to 10 minutes).

CLEAN UP

To remove smears of seam sealer from the carpet surface within 10 minutes use a clean cloth wet with soapy water. **Do not** apply soapy water directly on carpet. Clean with mineral spirits once dried. Use caution with mineral spirits which may be harmful to some materials.