

Product Information Declaration

Audacity Detail Trims Range

Range Description

This Jacobsen Product Information Declaration (PID) applies to the laminate range sold by Jacobsen as Audacity Detail Trims

Identifiers

See individual sku codes under [identifiers](#)

Scope and Limitations of Intended Use

<input checked="" type="checkbox"/> Residential	<input checked="" type="checkbox"/> Commercial	<input checked="" type="checkbox"/> Interior	<input checked="" type="checkbox"/> Exterior
<input checked="" type="checkbox"/> High Traffic	<input checked="" type="checkbox"/> Low-Traffic	<input checked="" type="checkbox"/> Exposed-Sunlight	<input checked="" type="checkbox"/> Wet Areas
<input checked="" type="checkbox"/> Antistatic Environment	<input checked="" type="checkbox"/> Food-Prep Areas	<input checked="" type="checkbox"/> Clean-Room	<input checked="" type="checkbox"/> With Wheels
<input checked="" type="checkbox"/> Ramp/Entry	<input checked="" type="checkbox"/> Under Floor Heating	<input checked="" type="checkbox"/> Over Existing Floor	

B Stability

Relevant NZBC Clause	Product Performance
B2.3.1(c)	15 years Limited Residential, 5 years Limited Commercial
Residential	AC4
Commercial	AC4
Industrial	-

C Protection from Fire

Relevant NZBC Clause	Product Performance
C4.3	
C4.3 (a) Wall	-
C4.3 (b) Floor	CHF >11 kW/m2 (ISO 9239.1:2010)

D Access

Relevant NZBC Clause	Product Performance
D1.3.3	
Level Surface (Wet)	-
Level Surface (Dry)	Acceptable Solution
Suitable for food prep	-

E Moisture

Relevant NZBC Clause	Product Performance
E3.3.3	Impervious and easily cleaned
E3.3.5	Impervious and easily cleaned
E3.3.6	Water resistant
NZBC/AS1	-

F Safety of Users

Relevant NZBC Clause	Product Performance
F2.3.1	≤ 0.5 mg/m3
	Does not encourage bacterial growth
	Phthalate-free
Indoor Air Quality	Optimal

G Services and Facilities

Relevant NZBC Clause	Product Performance
G3.3.2 (b)	Water resistant
G6.3.2	-

H Energy Efficiency

Relevant NZBC Clause	Product Performance
Thermal Rating	Not tested

X Warnings and Bans

Building Act 2004	Product Performance
Section 26	-

Supporting Documents

All supporting documents can be found on the Jacobsen website, jacobsen.co.nz or by this QR code



Product Information Declaration

Audacity Detail Trims Range

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c)
5 years if:
1. the building elements (including services, linings, renewable protective coatings, and fixtures) are easy to access and replace, and
 2. failure of those building elements to comply with the building code would be easily detected during normal use of the building.

C3.4

Surface Linings

(b)

floor surface materials in the following areas of buildings must meet the performance criteria specified below:

D1.3.3

Access routes shall:

(d)

have adequate slip-resistant walking surfaces under all conditions of normal use.

E3.3.3

Floor surfaces of any space containing sanitary fixtures or sanitary appliances must be impervious and easily cleaned.

E3.3.5

Surfaces of building elements likely to be splashed or become contaminated in the course of the intended use of the building, must be impervious and easily cleaned.

E3.3.6

Surfaces of building elements likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces.

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the construction of buildings, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b)

all building elements constructed with materials which are free from hazardous substances which could cause contamination to the building contents

G6.3.1

The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55.

G6.3.2

The Impact Insulation Class of floors shall be no less than 55.

H1

This clause requires enclosed spaces where temperature or humidity are modified to provide adequate thermal resistance and to limit uncontrollable airflow in certain buildings.

Note

It is expected that **Audacity Detail Trims** is installed, cleaned and maintained according to instructions and best practice guides housed on the product page.

All products may be subject to fading if exposed to excessive, unfiltered UV light.

Product Information Declaration

Audacity Detail Trims Range

Identifiers

This JPID covers all colours from Audacity Detail Trims including:

T Mould Victorian Oak 2.4m 22064	Reducer Castlepoint 2.4m 22097
T Mould Riverton 2.4m 22078	Reducer American Oak 2.4m 22074
Square Nose Helena Bay 2.4m 22104	Quarter Round Victorian Oak 2.4m 22160
Square Nose Foxton 2.4m 22113	Quarter Round Riverton 2.4m 22172
Square Nose Fiordland 2.4m 22119	Quarter Round Milford 2.4m 22170
Square Nose Eden 2.4m 22109	Quarter Round Mercury Bay 2.4m 22167
Square Nose Castlepoint 2.4m 22108	Quarter Round Longwood 2.4m 22161
Square Nose American Oak 2.4m 22105	Quarter Round London Fog 2.4m 22168
Reducer Victorian Oak 2.4m 22095	Quarter Round Helena Bay 2.4m 22158
Reducer Riverton 2.4m 22103	Quarter Round Foxton 2.4m 22169
Reducer Milford 2.4m 22102	Quarter Round Fiordland 2.4m 22176
Reducer Mercury Bay 2.4m 22099	Quarter Round Eden 2.4m 22166
Reducer Longwood 2.4m 22096	Quarter Round Castlepoint 2.4m 22165
Reducer London Fog 2.4m 22100	Stair Nosing Longwood 2.4m 22120
Reducer Helena Bay 2.4m 22073	Stair Nosing London Fog 2.4m 22153
Reducer Foxton 2.4m 22101	Stair Nosing Helena Bay 2.4m 22116
T Mould Milford 2.4m 22077	Stair Nosing Foxton 2.4m 22155
T Mould Mercury Bay 2.4m 22085	Stair Nosing Fiordland 2.4m 22175
T Mould Longwood 2.4m 22080	Stair Nosing Eden 2.4m 22122
T Mould London Fog 2.4m 22086	Stair Nosing Castlepoint 2.4m 22121
T Mould Helena Bay 2.4m 22062	Stair Nosing American Oak 2.4m 22088
T Mould Foxton 2.4m 22076	Square Nose Victorian Oak 2.4m 22106
T Mould Fiordland 2.4m 22081	Square Nose Riverton 2.4m 22115
T Mould Eden 2.4m 22084	Square Nose Milford 2.4m 22114
T Mould Castlepoint 2.4m 22083	Square Nose Mercury Bay 2.4m 22111
T Mould American Oak 2.4m 22063	Square Nose Longwood 2.4m 22107
Stair Nosing Victorian Oak 2.4m 22089	Square Nose London Fog 2.4m 22112
Stair Nosing Riverton 2.4m 22157	Quarter Round American Oak 2.4m 22159
Stair Nosing Milford 2.4m 22156	
Stair Nosing Mercury Bay 2.4m 22152	
Reducer Fiordland 2.4m 22118	
Reducer Eden 2.4m 22098	

Sustainability

Rating System	Rating	Product Performance
Green Star Design & As Built NZ (V1)	Credit 12	-
	Credit 20	-
	Credit 21	-
Green Star Interiors NZ (V1)	Credit 13	-
	Credit 20	-
	Credit 21	-
Green Star Performance NZ (V1)	Credit 21	-
Homestar V5	HC 7	1 Point
	EN 3	-
Homestar V4	Mat-1	-
	Mat-2	1 Point
Environmental Product Deceleration (EPD)		-
Embodied Carbon Emission Data		-

Environmental Credentials

Product Manufacturer: China Floors
Country of Origin: China

Jacobsen®

Jacobsen 41D Morrin Road,
St Johns, 1072
0800 800 460
jacobsen.co.nz
sales@jacobsen.co.nz

NZBN:
9429040403328